

View Online at <https://aerobasegroup.com/nsn/5320-01-249-9676>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.3110 inches and 0.3120 inches

**Shank Style:**

Self-plugging high clinch shank

**Head Major Diameter:**

0.558 inches

**Expansion Device:**

Expander

**Lubrication:**

Wax or stearic acid or dry film

**Grip Length:**

Between 0.594 inches and 0.656 inches

**Countersink Angle:**

60.0 degrees

**Special Features:**

Protrusion on head

**Heat Treatment:**

Annealed sleeve

**Material:**

Steel comp 4130 nut or steel comp 8740 nut or steel comp 4140 nut

**Material Specification:**

Mil-s-6758 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-5626 military specification 3rd material response nut

**Surface Treatment:**

Cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.