## NSN 5320-01-250-0667



Solid Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-250-0667 Fastener Length: Between 0.990 inches and 1.010 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.003 inches and 0.005 inches **Shank Diameter:** Between 0.124 inches and 0.127 inches **Shank Style:** Straight w/radius chamfered tip **Head Major Diameter:** 0.1957 inches **Head Minor Diameter:** 0.134 mils and 0.144 centimeters **Countersink Height:** 0.0286 inches **Shear Strength:** 24000 single pounds per square inch **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Heat Treatment:** H-32 strain hardened Material: Aluminum alloy 5056 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:** Anodize or chromate **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response **Specification Data:** 80205-nas1097 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

**Demilitarization:** 

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.