

View Online at <https://aerobasegroup.com/nsn/5320-01-250-3339>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Style:**

Self-plugging high clinch shank

**Head Major Diameter:**

0.439 inches

**Expansion Device:**

Expander

**Lubrication:**

Wax and stearic acid and dry film

**Grip Length:**

Between 1.219 inches and 1.281 inches

**Countersink Angle:**

60.0 degrees

**Special Features:**

Protrusion on head

**Heat Treatment:**

Annealed sleeve

**Material:**

Steel comp 4130 nut or steel comp 8740 nut or steel comp 4140 nut

**Material Specification:**

Ams 5641 assn standard 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve

**Surface Treatment:**

Cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.