# NSN 5320-01-250-3339

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-250-3339

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.2485 inches and 0.2495 inches

# Shank Style:

Self-plugging high clinch shank

# Head Major Diameter:

0.439 inches

## **Expansion Device:**

Expander

#### Lubrication:

Wax and stearic acid and dry film

## Grip Length:

Between 1.219 inches and 1.281 inches

## **Countersink Angle:**

60.0 degrees

# Special Features:

Protrusion on head

# Heat Treatment:

Annealed sleeve

# Material:

Steel comp 4130 nut or steel comp 8740 nut or steel comp 4140 nut

## Material Specification:

Ams 5641 assn standard 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve

#### Surface Treatment:

Cadmium sleeve

## Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response nut

#### Shelf Life:

N/a

# Unit Of Measure:

```
---
```

#### Demilitarization:

No

## Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.