Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-250-3878

Fastener Length:

0.250 inches

Head Style:

Countersunk w/ reverse chamfer

Head Height:

Between 0.035 inches and 0.045 inches

Hole Diameter:

Between 0.099 inches and 0.105 inches

Shank Diameter:

Between 0.141 inches and 0.146 inches

Shank Style:

Tubular

Head Major Diameter:

Between 0.289 inches and 0.303 inches

Hole Depth:

0.126 inches

Min. Tensile Strength (psi):

12000 pounds per square inch

Countersink Angle:

Between 149.0 degrees and 152.0 degrees

Material:

Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0