## NSN 5320-01-250-3878

Fiig: A040a0



Tubular Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-250-3878 **Fastener Length:** 0.250 inches **Head Style:** Countersunk w/ reverse chamfer **Head Height:** Between 0.035 inches and 0.045 inches **Hole Diameter:** Between 0.099 inches and 0.105 inches **Shank Diameter:** Between 0.141 inches and 0.146 inches **Shank Style:** Tubular **Head Major Diameter:** Between 0.289 inches and 0.303 inches **Hole Depth:** 0.126 inches Min. Tensile Strength (psi): 12000 pounds per square inch **Countersink Angle:** Between 149.0 degrees and 152.0 degrees Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:** No