NSN 5320-01-250-7989

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-250-7989 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.910 inches and 1.930 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.1198 inches and 0.1218 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3427 inches and 0.3432 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.6287 inches and 0.6335 inches Lubrication: Solid film and cetyl alcohol **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 12300 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 23200 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-250-7989

Pin-rivet - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A528u0