
## NSN 5320-01-250-9418

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.427 inches and 1.447 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.055 inches and 0.065 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.306 inches and 0.322 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and solid film

## Grip Length:

1.125 inches

## Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.164 inches

## Shear Strength:

4010 double pounds per square inch

#### Material:

Titanium alloy

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Anodize

## Surface Treatment Specification:

Ti-shield iii mfr ref single treatment response

## Thread Series Designator:

Unjc

#### Shelf Life:

N/a

# NSN 5320-01-250-9418

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

