

View Online at <https://aerobasegroup.com/nsn/5320-01-251-0008>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.228 inches and 0.230 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.378 inches and 0.385 inches

Expansion Device:

Threaded stem

Grip Length:

Between 0.595 inches and 0.656 inches

Min. Tensile Strength (psi):

1400 pounds per square inch

Shear Strength:

5240 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Qq-s-763 federal specification all material responses sleeve or ams5639 assn standard all material responses sleeve or ams5641 assn standard all material responses sleeve

Surface Treatment:

Passivate sleeve and cadmium sleeve and chromate sleeve

Surface Treatment Specification:

Qq-p-416 ty ii cl 2 federal specification all treatment responses nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.