

View Online at <https://aerobasegroup.com/nsn/5320-01-251-0008>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.228 inches and 0.230 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.378 inches and 0.385 inches

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.595 inches and 0.656 inches

**Min. Tensile Strength (psi):**

1400 pounds per square inch

**Shear Strength:**

5240 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

**Material Specification:**

Qq-s-763 federal specification all material responses sleeve or ams5639 assn standard all material responses sleeve or ams5641 assn standard all material responses sleeve

**Surface Treatment:**

Passivate sleeve and cadmium sleeve and chromate sleeve

**Surface Treatment Specification:**

Qq-p-416 ty ii cl 2 federal specification all treatment responses nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.