NSN 5320-01-251-0019

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-251-0019 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.094 inches and 1.114 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches **Grip Length:** Between 0.683 inches and 0.693 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 5820 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 9300 double pounds per square inch Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-251-0019

Pin-rivet - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A528u0