NSN 5320-01-251-0022



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-251-0022 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.144 inches and 1.164 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Grip Length:** Between 0.808 inches and 0.818 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 3180 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-251-0022

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0