NSN 5320-01-251-0950

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-251-0950

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.289 inches and 0.291 inches

Head Major Diameter:

Between 0.499 inches and 0.507 inches

Expansion Device:

Threaded stem

Lubrication:

Carbo wax or cetyl alcohol or dry film

Grip Length:

Between 0.657 inches and 0.719 inches

Min. Tensile Strength (psi):

3650 pounds per square inch

Shear Strength:

11800 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp h11 nut

Material Specification:

Ams5667 assn standard 1st material response sleeve or ams5582 assn standard 1st material response sleeve or ams5731 assn standard 2nd material response sleeve or ams5737 assn standard 2nd material response slee

Surface Treatment:

Cadmium sleeve

Surface Treatment Specification:

Qq-p-416, ty i, cls 3 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

```
---
```

Demilitarization:

No

Fiig:

A040a0