# NSN 5320-01-251-9288

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-251-9288



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Identification Code Color:

Natural

# Fastener Length:

Between 0.885 inches and 0.905 inches

#### Head Style:

Err-090

# Head Height:

Between 0.080 inches and 0.090 inches

# Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2641 inches and 0.2651 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

Between 0.387 inches and 0.412 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

0.505 inches

# Thready Qty Per Inch (tpi):

28

# Thread Size:

0.250 inches

# Heat Treatment:

T-6 solution heat treated

# Material:

Aluminum alloy 7075

# Material Specification:

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

# Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625 cl 2 military specification single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

# NSN 5320-01-251-9288

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.

