

View Online at <https://aerobasegroup.com/nsn/5320-01-252-0926>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.206 inches and 1.226 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**Grip Length:**

Between 0.870 inches and 0.880 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

3180 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

5380 double pounds per square inch

**Material:**

Titanium alloy

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0