NSN 5320-01-252-6067

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-252-6067

Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.3735 inches and 0.3745 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.672 inches
Expansion Device:
Threaded stem
Lubrication:
Carbo wax and stearic acid and dry film
Grip Length:
1.281 mils and 1.344 centimeters
Countersink Angle:
60.0 degrees
Special Features:
Protrusion on head
Heat Treatment:
Annealed sleeve
Material:
Steel comp 4130 nut or steel comp 8740 nut or steel comp 4140 nut
Material Specification:
Mil-s-6758 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-5626 military
specification 3rd material response nut
Surface Treatment:
Cadmium sleeve
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response nut
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-s-6758 spec.