NSN 5320-01-252-7799

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-252-7799
Identification Code Color:
Blue
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.178 inches and 0.180 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
Between 0.325 inches and 0.332 inches
Expansion Device:
Threaded sleeve
Grip Length:
Between 0.407 inches and 0.531 inches
Features Provided:
Self-locking Self-locking
Min. Tensile Strength (psi):
1350 pounds per square inch
Hardness Rating:
48.0 rockwell c nut and 53.0 rockwell c nut
Shear Strength:
4680 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
1/64 in. Oversize
Material:
Steel comp h11 nut
Material Specification:
Ams5667 assn standard 1st material response sleeve or ams5582 assn standard 1st material response sleeve or ams5731 assn standard
2nd material response sleeve or ams5732 assn standard 2nd material response sleeve or ams5737 assn standard 2nd material response
sleeve
Surface Treatment:
Cadmium sleeve
Surface Treatment Specification:
Qq-p-416, typ 1, cls 3 federal specification single treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A040a0

No