Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-252-7802

Identification Code Color:

Black

Head Style:

Hexagon

Head Height:

0.160 inches

Shank Diameter:

Between 0.3095 inches and 0.3115 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded sleeve

Grip Length:

Between 0.345 inches and 0.406 inches

Width Across Flats:

Between 0.429 inches and 0.437 inches

Features Provided:

Self-locking

Min. Tensile Strength (psi):

5200 pounds per square inch

Hardness Rating:

48.0 rockwell c bolt and 53.0 rockwell c bolt

Shear Strength:

17000 double pounds per square inch

Material:

Steel comp h11 nut

Material Specification:

Ams5667 assn standard 1st material response sleeve or ams5582 assn standard 1st material response sleeve or ams5731 assn standard 2nd material response sleeve or ams5737 assn standard 2nd material response slee

Surface Treatment:

Cadmium sleeve

Surface Treatment Specification:

Qq-p-416, typ i, cls 3 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0