## NSN 5320-01-253-3749



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-253-3749 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.973 inches and 1.013 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style: Head Major Diameter:** 0.305 inches **Grip Length:** Between 0.626 inches and 0.688 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Shear Strength:** 156000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas4452 professional/industrial association standard Shelf Life:

**Unit Of Measure:** 

N/a

## NSN 5320-01-253-3749

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0