# NSN 5320-01-253-4204

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-253-4204



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.850 inches and 0.870 inches

## Head Style:

Flush countersunk

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

## Shank Diameter:

Between 0.2177 inches and 0.2182 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.325 inches and 0.330 inches

# Grip Length:

Between 0.495 inches and 0.505 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

2000 pounds per square inch

# Thread Size:

0.190 inches

## Shear Strength:

7100 double pounds per square inch

## **Countersink Angle:**

100.0 degrees

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

## **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### **Demilitarization:**

No

## Fiig:

A528u0