# NSN 5320-01-253-5739

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-253-5739

| Head Style |  |
|------------|--|

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

#### **Shank Diameter:**

Between 0.289 inches and 0.291 inches

# **Head Major Diameter:**

Between 0.499 inches and 0.507 inches

#### **Expansion Device:**

Threaded stem

#### Lubrication:

Carbo wax or cetyl alcohol or dry film

#### **Grip Length:**

Between 0.782 inches and 0.844 inches

### Min. Tensile Strength (psi):

3650 pounds per square inch

#### **Shear Strength:**

11800 double pounds per square inch

# **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp h11 nut

# **Material Specification:**

Ams5667 assn standard 1st material response sleeve or ams5582 assn standard 1st material response sleeve or ams5731 assn standard 2nd material response sleeve or ams5737 assn standard 2nd material response sleeve or ams5737 assn standard 2nd material response sleeve

#### **Surface Treatment:**

Cadmium sleeve

# **Surface Treatment Specification:**

Qq-p-416, ty i, cls 3 federal specification single treatment response sleeve

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

A040a0