# NSN 5320-01-253-6632

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.503 inches and 0.523 inches

## Head Style:

Err-090

#### **Head Height:**

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Solid film

## End Application:

Aircraft, eagle f-15, aircraft, stratolifter c-135, aircraft, thunderbolt ii, a-10, aircraft, galaxy c-5

#### Grip Length:

0.193 inches

## Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.190 inches

# Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp xm-13

## Material Specification:

Ams 5629 assn standard single material response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-253-6632

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

