## NSN 5320-01-253-7170

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-253-7170 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.427 inches and 0.447 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.060 inches Width Between Flats: Between 0.0635 inches and 0.0645 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches Lubrication: Solid film **Grip Length:** 0.130 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-253-7170

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.