## NSN 5320-01-253-9067



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-253-9067 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.847 inches and 0.867 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5604 inches Lubrication: Cetyl alcohol **Grip Length:** 0.317 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** White paint on head Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

**Shelf Life:** N/a

## NSN 5320-01-253-9067

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0