
# NSN 5320-01-254-2594

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.802 inches and 0.822 inches

# Head Style:

Err-090

#### **Head Height:**

Between 0.068 inches and 0.078 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.317 inches

# Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.312 inches

## Shear Strength:

95000 single pounds per square inch

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

#### Surface Treatment:

Passivate

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-254-2594

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

