## NSN 5320-01-254-3800

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-254-3800 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.005 inches and 1.035 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2440 inches and 0.2485 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3898 inches and 0.3948 inches **Grip Length:** Between 0.390 inches and 0.400 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Hi-shear specification 306, type 1 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-254-3800

Pin-rivet - Page 2 of 2



Fiig:

A528u0