# NSN 5320-01-254-5455

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-254-5455



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.864 inches and 0.884 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.037 inches and 0.047 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.242 inches and 0.262 inches

### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 0.557 inches and 0.567 inches

#### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.164 inches

# Shear Strength:

125000 single pounds per square inch

# Material:

Steel comp xm-13

# Material Specification:

As 5629 assn standard single material response

## Surface Treatment:

Passivate

# Surface Treatment Specification:

258, cagec 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjc

Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 5320-01-254-5455

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

