NSN 5320-01-254-6602

Pin-rivet - Page 1 of 2

73197-hl10 manufacturers standard



View Online at https://aerobasegroup.com/nsn/5320-01-254-6602

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 1.015 inches and 1.025 inches
Head Style:
Err-090
Head Height:
Between 0.059 inches and 0.069 inches
Width Between Flats:
Between 0.095 inches and 0.097 inches
Shank Diameter:
Between 0.248 inches and 0.250 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.387 inches and 0.412 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.620 inches and 0.630 inches
Thread Size:
0.250 inches
Shear Strength:
9300 double pounds per square inch
Special Features:
U/w collars hi70, hi79, hi82, hi94k, hi94v, hi97k, hi97v, hi379v and hi379sy
Heat Treatment:
As fabricated
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment Specification:
Spec 306, type 1, color blue mfr ref single treatment response
Thread Series Designator:
Unjf
Specification Data:

NSN 5320-01-254-6602

Pin-rivet - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0