NSN 5320-01-254-7322

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-254-7322

Head Style:

Hexagon

Head Height:

0.135 inches

Shank Diameter:

Between 0.2641 inches and 0.2651 inches

Expansion Device:

Threaded sleeve

Grip Length:

Between 0.470 inches and 0.531 inches

Width Across Flats:

Between 0.367 inches and 0.375 inches

Features Provided:

Self-locking

Min. Tensile Strength (psi):

2100 pounds per square inch

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Shear Strength:

9000 double pounds per square inch

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams5639 assn standard 2nd material response sleeve or ams5641 assn

standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416, typ ii, cls 2 federal specification all treatment responses nut

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.