NSN 5320-01-254-7336

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-254-7336

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.325 inches and 1.355 inches

Head Style:

Err-090

Head Height:

Between 0.102 inches and 0.112 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Grip Length:

Between 0.807 inches and 0.817 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Shear Strength:

14600 double pounds per square inch

Material:

Titanium alloy

Material Specification:

Ams4928 assn standard single material response or ams4962 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 11, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No



NSN 5320-01-254-7336

Pin-rivet - Page 2 of 2

Fiig: A528u0

