NSN 5320-01-255-1099

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-255-1099

| Thread Class: |
|--|
| 3b |
| Thread Direction: |
| Right-hand |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| 0.387 inches |
| Shank Style: |
| Blind rivet, nut and bolt (assembly) |
| Head Major Diameter: |
| 0.445 inches |
| Expansion Device: |
| Threaded sleeve |
| Grip Length: |
| 0.375 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.250 inches |
| Countersink Angle: |
| Between 98.0 degrees and 102.0 degrees |
| Special Features: |
| Furnished with locking type expander and without bolt |
| Heat Treatment: |
| Annealed sleeve |
| Material: |
| Steel comp 303 expander |
| Material Specification: |
| Qq-a-430 federal specification single material response sleeve |
| Surface Treatment: |
| Cadmium expander |
| Surface Treatment Specification: |
| Qq-p-416, type 1, cl 3 federal specification single treatment response expander |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5320-01-255-1099

Blind Rivet - Page 2 of 2



Fiig:

A040a0