## NSN 5320-01-256-4509

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-256-4509 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.573 inches and 0.593 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5066 inches Lubrication: Cetyl alcohol **Grip Length:** 0.193 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 210000 pounds per square inch **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees Material: Steel comp 431 **Material Specification:** Ams 5628 assn standard single material response or mil-s-18732 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-256-4509

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.