NSN 5320-01-257-8643

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-257-8643

Identification Code Color:

Blue and yellow

Fastener Length:

0.891 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.139 inches and 0.143 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.221 inches and 0.229 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.313 inches and 0.375 inches

Features Provided:

Self-locking

Min. Tensile Strength (psi):

675 pounds per square inch

Shear Strength:

1090 single pounds per square inch

Countersink Angle:

108.0 degrees

Material:

Nickel alloy 400 sleeve

Material Specification:

Qq-n-281 uns n04400 federal specification single material response sleeve

Surface Treatment:

Passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses stem

Supplementary Features:

Replacement for nas 1921 rivet

Specification Data:

17446-osmls100 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5320-01-257-8643

Blind Rivet - Page 2 of 2

Fiig: A040a0

