

View Online at <https://aerobasegroup.com/nsn/5320-01-257-8645>

**Identification Code Color:**

Blue and yellow

**Fastener Length:**

0.500 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.200 inches and 0.204 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.349 inches and 0.357 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.100 inches and 0.125 inches

**Features Provided:**

Self-locking

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Shear Strength:**

2395 single pounds per square inch

**Countersink Angle:**

108.0 degrees

**Material:**

Nickel alloy 400 sleeve

**Material Specification:**

Qq-n-281 uns n04400 federal specification single material response sleeve

**Surface Treatment:**

Passivate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses stem

**Supplementary Features:**

Replacement for nas 1921 rivet

**Specification Data:**

17446-osmls100 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0