## NSN 5320-01-257-8645

Blind Rivet - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5320-01-257-8645

Identification Code Color:
Blue and yellow
Fastener Length:
0.500 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.200 inches and 0.204 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.349 inches and 0.357 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.100 inches and 0.125 inches
Features Provided:
Self-locking
Min. Tensile Strength (psi):
1500 pounds per square inch
Shear Strength:
2395 single pounds per square inch
Countersink Angle:
108.0 degrees
Material:
Nickel alloy 400 sleeve
Material Specification:
Qq-n-281 uns n04400 federal specification single material response sleeve
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses stem
Supplementary Features:
Replacement for nas 1921 rivet
Specification Data:
17446-osmls100 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

## NSN 5320-01-257-8645

Blind Rivet - Page 2 of 2



Fiig:

A040a0