

View Online at <https://aerobasegroup.com/nsn/5320-01-257-9781>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.8700 inches and 0.8800 inches

**Head Style:**

Err-090

**Width Between Flats:**

0.1270 inches

**Shank Diameter:**

0.3115 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.4689 inches

**Lubrication:**

Solid film and cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.3700 inches and 0.3800 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.3125 inches

**Shear Strength:**

14600 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

White federal standard 595 color no 37875

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Ti-shield 3, cagec 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0