

View Online at <https://aerobasegroup.com/nsn/5320-01-258-8256>

**Fastener Length:**

0.844 inches

**Head Style:**

Tapered pan

**Head Height:**

Between 0.062 inches and 0.070 inches

**Shank Diameter:**

Between 0.162 inches and 0.164 inches

**Head Major Diameter:**

Between 0.250 inches and 0.272 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.719 inches and 0.782 inches

**Features Provided:**

Self-locking

**Min. Tensile Strength (psi):**

1350 pounds per square inch

**Hardness Rating:**

48.0 rockwell c stem and 53.0 rockwell c stem

**Shear Strength:**

2340 single pounds per square inch

**Material:**

Steel comp 8740 stem

**Material Specification:**

Astm a331, uns g87400 assn standard single material response stem

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 1, class 3 federal specification single treatment response stem

**Supplementary Features:**

U/w installation tooling mil-f-81177, appendix a

**Specification Data:**

96906-ms90354 government standard and 17446-ubp-t manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0