## NSN 5320-01-259-1285

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-259-1285 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.8775 inches and 0.8975 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.5575 inches and 0.5675 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Anodize **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-259-1285

Pin-rivet - Page 2 of 2



Fiig:

A528u0