NSN 5320-01-259-4103

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-259-4103 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.308 inches and 1.333 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.080 inches **Shank Diameter:** 0.3417 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.490 inches and 0.502 inches Tip Diameter: 0.3241 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.927 inches and 0.942 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 4340 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1728 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-01-259-4103

Pin-rivet - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A528u0