NSN 5320-01-259-9148

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-259-9148 **Fastener Length:** Between 0.177 inches and 0.197 inches **Head Style:** Err-090 **Head Height:** 0.050 inches **Shank Diameter:** Between 0.1865 inches and 0.1890 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.292 inches and 0.322 inches **Unable To Decode:** Unable to decode and unable to decode **Unable To Decode:** Unable to decode and unable to decode **Grip Length:** 0.062 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4140 or steel comp 4130 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or ams 6382 assn standard 1st material response or mil-s-6758 military specification 2nd material response or ams 6370 assn standard 2nd material response or mil-s-6049 military specification 3rd material response or ams 6322 assn standard 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, cl 2 federal specification single treatment response Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A528u0

No

Mil-std (military Standard):

Mil-s-5626 spec.