

View Online at <https://aerobasegroup.com/nsn/5320-01-263-4360>

**Fastener Length:**

Between 0.632 inches and 0.662 inches

**Head Style:**

Universal

**Head Height:**

Between 0.054 inches and 0.064 inches

**Shank Diameter:**

Between 0.125 inches and 0.129 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.240 inches and 0.260 inches

**Expansion Device:**

Serrated stem-type w

**End Application:**

Low altitute navigation & targeting infrared syste (lantirn) ; helicopter, lamps mark iii, sh-60b; aircraft, hercules c-130; milstar system

**Grip Length:**

0.501 mils and 0.562 centimeters

**Special Features:**

"ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.

**Material:**

Steel comp 8740 stem

**Material Specification:**

Qq-a-430 federal specification single material response sleeve

**Surface Treatment:**

Cadmium stem and chromate stem

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.