## NSN 5320-01-263-5656

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-263-5656 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.6275 inches and 0.6475 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.3075 inches and 0.3175 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Furnished w/collar Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment Specification:** Hi-shear specification 306 tyi color blue mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

## NSN 5320-01-263-5656

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0