## NSN 5320-01-265-8248

Pin-rivet - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5320-01-265-8248 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.740 inches and 1.760 inches **Head Style:** Err-090 **Head Height:** Between 0.098 inches and 0.112 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.472 inches and 0.502 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.255 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response or ams 5731 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

## NSN 5320-01-265-8248

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0