

View Online at <https://aerobasegroup.com/nsn/5320-01-266-2573>

Head Style:

Universal

Head Height:

Between 0.067 inches and 0.077 inches

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Self-plugging high clinch shank

Head Major Diameter:

Between 0.296 inches and 0.328 inches

Expansion Device:

Plain stem-type t

Grip Length:

0.251 mils and 0.375 centimeters

Material:

Steel comp 1006 stem or steel comp 1008 stem or steel comp 1010 stem or steel comp 1012 stem or steel comp 1015 stem or steel comp 1016 stem or steel comp 1018 stem or steel comp 1019 stem or steel comp 1021 stem or steel comp 1022 stem or steel comp 1026 stem or steel comp 1030 stem or steel comp 1035 stem or steel comp 1038 stem or steel comp 1524 stem or steel comp 1541 stem

Material Specification:

Mil-w-7986 military specification single material response sleeve

Surface Treatment:

Anodize sleeve or chromate sleeve

Surface Treatment Specification:

Mil-a-8625, type 2, cl 1 military specification 1st treatment response sleeve or mil-c-5541, cl 1a military specification 2nd treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-w-7986 spec.