## NSN 5320-01-266-4730

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-266-4730



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.377 inches and 1.397 inches

## Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

1.067 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## Shear Strength:

125000 single pounds per square inch

## **Special Features:**

White paint on head

#### Material:

Steel comp xm-13

## **Material Specification:**

Ams 5629 assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

258, cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

# NSN 5320-01-266-4730

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

