NSN 5320-01-267-7550

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-267-7550 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.896 inches and 0.921 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.080 inches **Shank Diameter:** 0.3703 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.533 inches and 0.544 inches Tip Diameter: 0.3619 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.490 inches and 0.505 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.3125 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp xm-13 **Material Specification:** Qq-p-35 federal specification single treatment response

Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification: Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-267-7550

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0