# NSN 5320-01-267-8517

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-267-8517



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.006 inches and 1.032 inches

# Head Style:

Err-090

## Head Height:

Between 0.082 inches and 0.094 inches

## Shank Diameter:

0.4381 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.628 inches and 0.642 inches

#### **Tip Diameter:**

0.4284 inches

## Lubrication:

Dry film and cetyl alcohol

#### Grip Length:

Between 0.552 inches and 0.567 inches

# Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

220000 pounds per square inch

#### **Thread Size:**

0.375 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp xm-13

#### **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# NSN 5320-01-267-8517

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

