## NSN 5320-01-268-0001

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-268-0001

| 0.100 inches  Head Style:  Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)  Hole Diameter: |
|---|
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)  |
|   |
| Hole Diameter:  |
|   |
| Between 0.039 inches and 0.044 inches   |
| Shank Diameter:   |
| Between 0.058 inches and 0.061 inches   |
| Shank Style:  |
| Tubular   |
| Head Major Diameter:  |
| Between 0.100 inches and 0.110 inches   |
| Hole Depth:   |
| Between 0.046 inches and 0.056 inches   |
| Countersink Angle:  |
| 100.0 degrees   |
| Material:   |
| Steel comp 303  |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Qq-p-35 federal specification single treatment response   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A040a0  |
|   |
|   |
|   |