## NSN 5320-01-268-5600

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-268-5600



## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.896 inches and 0.921 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.068 inches and 0.080 inches

#### Shank Diameter:

0.3560 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

0.524 inches

### Tip Diameter:

0.3476 inches

#### Lubrication:

Dry film and cetyl alcohol

### Grip Length:

Between 0.490 inches and 0.505 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

220000 pounds per square inch

## Thread Size:

0.3125 inches

## Shear Strength:

125000 single pounds per square inch

## Material:

Steel comp xm-13

## Material Specification:

Ams 5629 assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-268-5600

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

