## NSN 5320-01-268-6892

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-268-6892 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.697 inches and 1.717 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.307 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 45.0 rockwell c and 48.0 rockwell c **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, type 2, cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-268-6892

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.